

## FLEX - F100 - W/S - 3/6 K



| Watt | LM   | CRI | Cut   | IP   | CLS  |
|------|------|-----|-------|------|------|
| 15   | 1200 | >82 | 100mm | IP20 | IC-F |

### Specifications

|               |                       |
|---------------|-----------------------|
| Material:     | Aluminium             |
| Body Size:    | (mm) 100*75           |
| Voltage:      | 220-240 VAC 50Hz      |
| Chip Brand:   | Epistar SMD           |
| Lifespan:     | >/=50000HRS           |
| Trim Colours: | White & Silver finish |

### Technical information

|                       |                          |
|-----------------------|--------------------------|
| Fitting:              | 1* diffused LED - Gamble |
| Driver:               | Dimmable Driver          |
| Total power consumed: | 15 Watt                  |
| Power factor:         | >0.9                     |
| Lumens flux:          | 1200 LM                  |
| Beam Angle:           | 120 degrees              |
| CRI:                  | >82                      |
| Colour Temperature    | Warm White 3000K         |

### Instalment information

|                   |       |
|-------------------|-------|
| Cutout Hole:      | 100mm |
| Overall Diameter: | 120mm |
| Install Depth:    | 75mm  |

*Note: Specifications given for 3000K. Specifications for Cool White differ slightly*