

ORBIT TRADING LIMITED



PRODUCTS LIST

October 2017

All Products Are
New Zealand
Australian Standard

Greeting from LEDX

ORBIT TRADING LIMITED (**OTL**) is a New Zealand lighting technology and solution provider. We innovate, design, manufacture and Supply new lightening technologies. As a member of the New Zealand Lighting Council, our strict quality standard (SQS) committed to provide the most environmentally friendly materials / products to the market. **LEDX**, our first range of LED in New Zealand.

Please feel free to:

Visit our showroom between 8am to 4pm Monday - Friday

Call, Text or Email us as follow:

TEL: +6499744868

Cell: +6421 295 6704

E: sales@ledx.co.nz

DOWNLIGHT

DELTA: DL95

- ASNZ Standard - Dimmable - IC-F - IP44 - 95 mm cutout - 110mm Overall Diameter - 48mm Depth - Beam angle 120 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
DL95W313	13	1040	>82	95mm	IP44	>0.9	3000K
DL95W613	13	1040	>82	95mm	IP44	>0.9	6000K

ELEGANT: E95

- ASNZ Standard - Dimmable - IC-F - IP44 - 95 mm cutout - 110mm Overall Diameter - 48mm Depth - Beam angle 120 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
E95W314	14	1120	>82	95mm	IP44	>0.9	3000K
E95W614	14	1120	>82	95mm	IP44	>0.9	6000K
E95S314	14	1120	>82	95mm	IP44	>0.9	3000K
E95S614	14	1120	>82	95mm	IP44	>0.9	6000K



DL95



DL95



E95W



E95S



FLEX: F92 F95 F100

- ASNZ Standard - Dimmable - IC-F - IP20 - 92/95/100 mm cutout - 100/110/120mm Overall Diameter - 50/100/75mm Depth - Beam angle 120/60 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
F92W313	13	1040	>82	92mm	IP20	>0.9	3000K
F92W613	13	1040	>82	92mm	IP20	>0.9	6000K
F95W315	15	1040	>82	95mm	IP20	>0.9	3000K
F95W615	15	1040	>82	95mm	IP20	>0.9	6000K
F100W315	15	1200	>82	100mm	IP20	>0.9	3000K
F100W615	15	1200	>82	100mm	IP20	>0.9	6000K

JUMBO: J120 / J150

- ASNZ Standard - Dimmable - IC-F - IP44 - 120/150 mm cutout - 140/159mm Overall Diameter - 48/60mm Depth - Beam angle 120 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
J120W315	15	1200	>82	120mm	IP44	>0.9	3000K
J120w615	15	1200	>82	120mm	IP44	>0.9	6000K
J120S315	15	1200	>82	120mm	IP44	>0.9	3000K
J120S615	15	1200	>82	120mm	IP44	>0.9	6000K
J150W320	20	1800	>82	150mm	IP44	>0.9	3000K
J150W620	20	1800	>82	150mm	IP44	>0.9	6000K



F95W



F92W



J120S



J150W

KENT: K90

ASNZ Standard - Dimmable - IC-F - IP44 - 90 mm cutout - 108mm Overall Diameter - 31mm Depth - Beam angle 120 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
K90W313	13	1040	>82	90mm	IP44	>0.9	3000K
K90W613	13	1040	>82	90mm	IP44	>0.9	6000K
K90S313	13	1040	>82	90mm	IP44	>0.9	3000K
K90S613	13	1040	>82	90mm	IP44	>0.9	6000K

KENT: K70

- ASNZ Standard - Dimmable - IC-F - IP44 - 70 mm cutout - 85mm Overall Diameter - 31mm Depth - Beam angle 120 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
K70W309	9	700	>82	70mm	IP44	>0.9	3000K
K70W609	9	700	>82	70mm	IP44	>0.9	6000K
K70S309	9	700	>82	70mm	IP44	>0.9	3000K
K70S609	9	700	>82	70mm	IP44	>0.9	6000K

MARINE: M95

- ASNZ Standard - Dimmable - IC-F - IP65 - 95 mm cutout - 105mm Overall Diameter - 50mm Depth - Beam angle 120 Degrees

Code	Watt	LM	CRI	Cut	IP	PF	Temp
M95W315	15	1200	>82	95mm	IP65	>0.9	3000K
M95W615	15	1200	>82	95mm	IP66	>0.9	6000K



K90W



K90S



K70S



K70W



M95W



M95W

CEILING LIGHTS

Clutha: CL

- ASNZ Standard

Code	Watts	LM	CRI	Cut	IP	PF
CL280CC	18	1500	>82	280mm	54	>0.9
CL150CC	15	1250	>82	156mm	20	>0.9
CL280CBH	18	1500	>82	280mm	54	>0.9
CL330CBH	24	2050	>82	330mm	54	>0.9
CL400CBH	36	2900	>82	400mm	54	>0.9
CL230BH	12	1050	>82	230mm	65	>0.5
CL230CBH	12	1050	>82	230mm	65	>0.7



CL230CBH



CL400CBH



CL280CC

TUBE LIGHTS

SLIM: SN

ASNZ Standard - IP22 - 1 Year warranty - 3000K - 4200K - 6000K

Code	Watt	LM	Body Size
SN18	18	1500 ± 5%	71x31x18mm
SN27	27	2000 ± 5%	100.5x31x18mm
SN36	36	2600 ± 5%	1200x31x18mm

TRIO: TR

ASNZ Standard - IP65 - 3 Year warranty - 6000K

Code	Watt	LM	Body Size
TR2060	20	1800	71x24.5x25.5mm
TR4060	40	3600	131x24.5x25.5x5mm
TR5060	50	4500	161x24.5x25.5x5mm

Linear: SLH/T

ASNZ Standard - IP42 - 3 Year warranty White and Silver frame

Code	Watt	LM	Body Size
SLHL40B	40	5200	1200x73x55mm
SLHL60B	60	7800	1500x73x55mm



TR 20/40/50



TR 20/40/50



SLHL40B



SN 18/27/36

FLOODLIGHTS

- ASNZ Standard - SAA approved - IP65 - 5 Year extensive warranty
- Beam Angle 130 degrees

SFL

Code	Watt	LM	Dimensions
SFL10B	10	950	130x96x30mm
SFL10BS	10	950	130x96x30mm
SFL20B	20	1900	200x137x36mm
SFL20BS	20	1900	200x137x36mm
SFL30B	30	2850	248x160x47mm
SFL30BS	30	2850	248x160x47mm
SFL50B	50	4750	248x160x47mm
SFL50BS	50	4750	248x160x47mm
SFL100B	100	9500	300x204x57mm
SFL150B	150	14000	360x233x37mm
SFL180B	180	23000	360x233x37mm
SFL200B	200	25000	360x233x37mm
UFL150B	150	19500	360x233x37mm
UFL200B	200	26000	360x233x37mm



SFL50B



SFL30B



UFL150B

HIGH BAY LIGHTS

- ASNZ Standard - SAA approved - IP65 - 5 Year extensive warranty
- Beam Angle 120 degrees

UFO

Code	Watt	LM
UFO100HB	100	13000
UFO150HB	150	19500
UFO200HB	200	26000
UFO240HB	240	31200



UFO240HB



UFO150HB

PANEL LIGHTS

Panel Lights: PN12060

- Full accessories - 5 Years warranty - Warm White and Cool White

Code	Watt	LM	Beam	CRI	Size
PN12060CW	72	6500	100	80	1195*595*10mm
PN12060WW	72	6500	100	80	1195*595*10mm

PN12030

Code	Watt	LM	Beam	CRI	Size
PN12030CW	40	3600	100	80	1200x300x5mm
PN12030WW	40	3600	100	80	1200x300x5mm

PN6060

Code	Watt	LM	Beam	CRI	Size
PN6060CW	42	3600	100	80	600x600x10mm
PN6060WW	42	3600	100	80	600x600x10mm



PN12060W



PN6060W



PN12030W

